





CODE	DESCRIPTION
CA-TP32 	BENCH TOP HIGH FIBER PUREE MACHINE <i>Able to process over mature roots, allow for high output with no peeling required. Stainless steel 18/8 cutting group. Removable hopper and mincing group to be rapidly cleaned. Reduction gears in hardened and grinded steel, running in oil bath. Fan cooled motor for continuous service. Reserving switch to release the blocked elements in the cutting group with no need of dismantling the machine. Solid structure in first quality stainless steel, fitted in stainless steel housing on wheels. No corner or dust traps. Constructed according to EN 12331 rules. Easy to Assemble Bench Top: production output 250kgs per hour.</i>
P-FA 	STEAMING VAT <i>Indirect Heating. Autoclave lid. Analog Control. Build in Stainless steel Dimension ((L x P x H) mm 900x850x900 Tank capacity 150 Liters Electric power Kw 13 Voltage 380-415V 3N ~ 50Hz</i>
MVS45 XP 	TABLETOP VACUUM SEALING MVS45 XP: the chamber vacuum sealer with tracking of internal vacuum <i>With the new MVS XP line the vacuum inside the package can be traced: it is a new and revolutionary concept for the internal vacuum, an exclusive innovation in the minipack®-torre style.</i> TECHNICAL FEATURES <i>Electrical power supply 230 volt Dimensions of sealing bars MVS45 XP 450 mm Packaging cycle (Vacuum 20%) Vacuum =24 sec, Air remission = 8 sec Vacuum pump 20 mc/h Machine dimensions with the lid open 544X649 H750 mm Machine dimensions with the lid closed 544X649 H490 mm</i>

CA-TP32 	BENCH TOP HIGH FIBER PUREE MACHINE X 2PCS <i>Able to process over mature roots, allow for high output with no peeling required. Stainless steel 18/8 cutting group. Removable hopper and mincing group to be rapidly cleaned. Reduction gears in hardened and grinded steel, running in oil bath. Fan cooled motor for continuous service. Reserving switch to release the blocked elements in the cutting group with no need of dismantling the machine. Solid structure in first quality stainless steel, fitted in stainless steel housing on wheels. No corner or dust traps. Constructed according to EN 12331 rules. Easy to Assemble Bench Top: production output 250kgs per hour.</i>
---	---